# 998 Set Cancellation

Functional Group ID=AL

### **Introduction:**

This Draft Standard for Trial Use contains the format and establishes the data contents of the Set Cancellation Transaction Set (998) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to request the deletion of a previously transmitted transaction set and will indicate the reason for this action, such as diversion or cancelled bill.

Page	Pos.	Seg.		Req.		Loop	Notes and
No.	No.	<u>ID</u>	<u>Name</u>	Des.	Max.Use	Repeat	<b>Comments</b>
2	010	ST	Transaction Set Header	M	1		
3	020	ZD	Transaction Set Deletion - ID, Reason, and Source	M	1		
4	030	SE	Transaction Set Trailer	M	1		

004010F998A0 May 8, 2001

Segment: ST Transaction Set Header

**Position:** 010

Loop:

Level:

**Usage:** Mandatory

Max Use: 1

**Purpose:** To indicate the start of a transaction set and to assign a control number

Syntax Notes:

**Semantic Notes:** 1 The transaction set identifier (ST01) is used by the translation routines of the

interchange partners to select the appropriate transaction set definition (e.g.,

810 selects the Invoice Transaction Set).

**Comments:** 

#### **Data Element Summary**

M	Ref. <u>Des.</u> ST01	Data Element 143	Name Transaction Set Identifier Code	Attributes M ID 3/3	
			Code uniquely identifying a Transaction Set  998 Set Cancellation		
M	ST02	329	<b>Transaction Set Control Number</b>	M AN 4/9	
			Identifying control number that must be unique within the transactio functional group assigned by the originator for a transaction set		

Segment: **ZD** Transaction Set Deletion - ID, Reason, and Source

**Position:** 020

Loop:

Level:

Usage: Mandatory

Max Use: 1

**Purpose:** This segment is used to specify the transaction set to be canceled

Syntax Notes: Semantic Notes: Comments:

#### **Data Element Summary**

Data Element Summary						
	Ref.	Data				
	Des.	<b>Element</b>	<u>Name</u>	<u>Att</u>	<u>ributes</u>	
$\mathbf{M}$	<b>ZD01</b>	143	Transaction Set Identifier Code	$\mathbf{M}$	ID 3/3	
			Code uniquely identifying a Transaction Set			
			404 Rail Carrier Shipment Information			
Not Used	<b>ZD02</b>	145	<b>Shipment Identification Number</b>	O	AN 1/30	
			Identification number assigned to the shipment by the shipper that uniquely identifies the shipment from origin to ultimate destination and is not subject to modification; (Does not contain blanks or special characters)			
M	<b>ZD03</b>	206	<b>Equipment Initial</b>	M	AN 1/4	
			Prefix or alphabetic part of an equipment unit's identifying number			
M	<b>ZD04</b>	207	<b>Equipment Number</b>	M	AN 1/10	
			Sequencing or serial part of an equipment unit's identifyin numeric form for equipment number is preferred)	g nui	mber (pure	
Must Use	<b>ZD05</b>	244	<b>Transaction Reference Number</b>	0	AN 1/15	
			Sender's assigned number for referenced transaction set			
Must Use	<b>ZD06</b>	243	<b>Transaction Reference Date</b>	0	<b>DT 8/8</b>	
			Date of referenced transaction set expressed in format CCYYMMDD			
M	<b>ZD07</b>	202	Correction Indicator	M	ID 2/2	
			Code used to indicate that the transaction set contains info corrects previous information	rmat	ion which	
			CA Cancelled Bill			
Must Use	<b>ZD08</b>	140	Standard Carrier Alpha Code	0	ID 2/4	
			Standard Carrier Alpha Code			
			Refer to 004010 Data Element Dictionary for acceptable code values.			
	• •					

 ${\bf SE}$  Transaction Set Trailer **Segment:** 

030 **Position:** 

> Loop: Level:

Usage: Mandatory

Max Use:

**Purpose:** To indicate the end of the transaction set and provide the count of the transmitted

segments (including the beginning (ST) and ending (SE) segments)

**Syntax Notes:** 

**Semantic Notes:** 

**Comments:** 1 SE is the last segment of each transaction set.

## **Data Element Summary**

M	Ref. <u>Des.</u> SE01	Data <u>Element</u> 96	Name Number of Included Segments		ributes N0 1/10	
			Total number of segments included in a transaction set inc SE segments	ludir	ng ST and	
M	SE02	329	<b>Transaction Set Control Number</b>	M	AN 4/9	
			Identifying control number that must be unique within the transaction functional group assigned by the originator for a transaction set			